



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Silicone Spray

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

Zettex Silicone Spray is a high-quality silicon spray with 70 % of silicones. Zettex Silicone Spray can be used on all kind of surfaces and gives a durable protection.

Material

Silicones

Advantages

- Suitable for use on plastic and metals.
- Improved lubricating properties at high temperatures.
- Excellent penetrating properties.
- Odourless
- Colourless
- No other additives

Uses

Usually used on metals, plastic and most other impervious surfaces. In particular in the automotive market for the lubrication of locks, hinges, door rubbers, window channels, antennas, battery terminals and so-called squeaky locations.

Not for use in areas to be painted and in areas where corrosion protection is needed.

Application instructions

Shake well before use. Spray directly on the surface from a distance of approximately 20 to 30 cm. Remove excess lubricant with the Zettex Bonte or Witte tricot cloths. Clean hands with the Zettex Cleaning Wipes.

Available form

Spray can 500 ml

Colour

Transparent

Safety recommendations

This technical information does not contain an MSDS (Material Safety Data Sheet). You must first fully read the MSDS before using this product.

| Properties | Specification |
|----------------------------------|---|
| pH | Not applicable |
| Specific gravity | 0.810 – 0.830 |
| Viscosity | Slightly sticky liquid |
| Not volatile % m/m | 30-40 |
| Active content | 5-10 |
| Flammability | Highly ignitable, flash point below -20°C |
| Continuous operating temperature | 200 °C |

| | |
|------------------------------------|---------------|
| Intermittent operating temperature | 250 °C |
| Self-ignition temperature (°C) | 250 DIN 51794 |
| Explosion limits, Vol % lower | 1.1 DIN 51649 |