



Gas driven single point automatic lubricators SKF SYSTEM 24 – LAGD Series

The units are supplied ready-to-use straight from the box and filled with a wide range of high performance SKF lubricants. Tool-free activation and time-setting allow easy and accurate adjustment of lubrication flow.



- Flexible dispense rate from 1 to 12 months
- Stoppable or adjustable if required
- Intrinsic safety rating: ATEX approved for zone 0
- Transparent lubricant container allows visual inspection of dispense rate
- Compact size, permits installation in restrictive areas
- Greases and chain oils available
- SKF DialSet helps to calculate the correct dispense rate

Typical applications

- Applications in restrictive and hazardous locations
- Bearing housing lubrication
- Electric motors
- Fans and pumps
- Conveyors
- Cranes
- Chains (oil)
- Elevators and escalators (oil)



Technical data

Designation LAGD 60 and LAGD 125

Grease capacity	
– LAGD 60	60 ml (2 US fl. oz)
– LAGD 125	125 ml (4.2 US fl. oz)
Nominal emptying time	Adjustable; 1–12 months
Ambient temperature range	
– LAGD 60/.. and LAGD 125/..	–20 to +60 °C (–5 to +140 °F)
Maximum operating pressure	5 bar (75 psi) (at start-up)
Drive mechanism	Gas cell producing inert gas
Connection thread	R ¹ / ₄
Maximum feed line length with:	
– grease	300 mm (11.8 in.)
– oil	1 500 mm (59.1 in.)

Intrinsically safe approval	II 1 G Ex ia IICT6 Ga II 1 D Ex ia IICT85°C Da I M1 Ex ia I Ma
EC Type Examination Certificate	Kema 07ATEX0132 X
Protection class	IP 68
Recommended storage temperature	20 °C (70 °F)
Storage life of lubricator	2 years
Weight	LAGD 125 approx 200 g (7.1 oz) LAGD 60 approx 130 g (4.6 oz) Lubricant included

Note: For optimum performance, SKF SYSTEM 24 LAGD units filled with LGHP 2 should not be exposed to ambient temperatures over 40 °C (105 °F), or have a time setting longer than 6 months.

Ordering details

Grease	LGWA 2	LGEM 2	LGGB 2	LGHB 2	LGHP 2	LGFP 2	LGWM 2
Description	Multi-purpose EP type grease	High loads, slow rotations	Biodegradable	High temperature & loads, plain bearings	High performance polyurea	Food processing industry	High load, wide temperature
Unit 60 ml	LAGD 60/WA2	LAGD 60/EM2	–	LAGD 60/HB2	LAGD 60/HP2	LAGD 60/FP2	–
Unit 125 ml	LAGD 125/WA2	LAGD 125/EM2	LAGD 125/GB2	LAGD 125/HB2	LAGD 125/HP2	LAGD 125/FP2	LAGD 125/WM2

Chain oils	LHMT 68	LHHT 265	LHFP 150	–
Description	Medium temperature oil	High temperature oil	Food compatible, NSF H1 approved oil	Empty unit suitable for oil filling only
Unit 60 ml	LAGD 60/HMT68			LAGD 60/U
Unit 125 ml	LAGD 125/HMT68	LAGD 125/HHT26	LAGD 125/HFP15	LAGD 125/U

Note: For custom fillings, contact your SKF authorised distributor.

Accessories ordering details

Designation	Description
LAPA 45	Angle connection 45°
LAPA 90	Angle connection 90°
LAPE 35	Extension 35 mm
LAPE 50	Extension 50 mm
LAPF F ¹ / ₄	Tube connection female G ¹ / ₄
LAPF M ¹ / ₈	Tube connection male G ¹ / ₈
LAPF M ¹ / ₄	Tube connection male G ¹ / ₄
LAPF M ³ / ₈	Tube connection male G ³ / ₈
LAPG ¹ / ₄	Grease nipple G ¹ / ₄
LAPM 2	Y-connection
LAPN ¹ / ₈	Nipple G ¹ / ₄ – G ¹ / ₈
LAPN ¹ / ₄	Nipple G ¹ / ₄ – G ¹ / ₄
LAPN ¹ / ₂	Nipple G ¹ / ₄ – G ¹ / ₂
LAPN ¹ / ₄ UNF	Nipple G ¹ / ₄ – ¹ / ₄ UNF
LAPN ³ / ₈	Nipple G ¹ / ₄ – G ³ / ₈
LAPN 6	Nipple G ¹ / ₄ – M6
LAPN 8	Nipple G ¹ / ₄ – M8

Designation	Description
LAPN 8x1	Nipple G ¹ / ₄ – M8 × 1
LAPN 10	Nipple G ¹ / ₄ – M10
LAPN 10x1	Nipple G ¹ / ₄ – M10 × 1
LAPN 12	Nipple G ¹ / ₄ – M12
LAPN 12x1.5	Nipple G ¹ / ₄ – M12 × 1.5
LAPB 3x4E1	Brush 30 × 40 mm
LAPB 3x7E1	Brush 30 × 60 mm
LAPB 3x10E1	Brush 30 × 100 mm
LAPB 5–16E1	Elevator brush, 5–16 mm gap
LAPB D2	Brush round Ø20 mm
LAPV ¹ / ₄	Non-return valve G ¹ / ₄
LAPV ¹ / ₈	Non-return valve G ¹ / ₈
LAPC 50	Clamp
LAPP 4	Protection base
LAPP 6	Protection cap
LAPT 1000	Flexible tube, 1 000 mm long, 8 × 6 mm

© SKF is a registered trademark of the SKF Group.

© SKF Group 2016

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 12666 EN · January 2016

