

Radiator Stop-Leak

Description

Radiator Stop-Leak is a dispersion for sealing leaks in water-cooling systems in motor vehicles. The product reliably seals hair cracks and small leaks. The solids dispersion is stabilised in carrier fluid.

Properties

- compatible with conventional coolant water refiners and antifreezes
- suitable for aluminum radiators
- permanently and reliably seals hairline cracks and small leaks
- no negative side effects on the water pump or heating circuit
- for preventive use

Technical data

Form	flüssig / liquid
Color / appearance	je nach Spezifikation / according to specification
Density at 20 °C	1,07 g/cm ³
Solubility in water	mischbar / mixable
Odor	schwach / weak
Flash point	200 °C
Viscosity at 40 °C	130 mm ² /s

Areas of application

Used for sealing small leaks in cooling circuits of passenger motor vehicles, commercial vehicles, buses and two-wheel vehicles. Also suitable for cooling circuit with filters.

Application

Shake container before use. Run the heating system. With the engine running, pour the contents into the cooling fluid at operating temperature and allow the engine to continue running for a further 10 minutes. The contents is sufficient for 10 litres of coolant.



Available pack sizes

150 ml Can sheet metal	3330
	D-F-NL
150 ml Can sheet metal	2505
	D-E-P
150 ml Can sheet metal	8371
	GB-ARAB-F
150 ml Can sheet metal	8347
	D-PL-BG
150 ml Can sheet metal	8956
	GB-GR-I
150 ml Can sheet metal	7129
	ALGERIEN-GB-ARAB-F
250 ml Can sheet metal	2828
	DK/N-S-FIN
250 ml Can sheet metal	1810
	GB-GR-I
250 ml Can sheet metal	2676
	D-PL-BG
250 ml Can sheet metal	1921
	D-F-I
250 ml Can sheet metal	8370
	GB-ARAB-F
250 ml Can sheet metal	8385
	D-H-RO
250 ml Can sheet metal	1997
	D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.