

**MOLYSLIP (Canada) Inc.**  
20-1145 Bellamy Road North  
Scarborough, ON M1H 1H5  
Canada

T: 416-438-5523  
1-800-880-MOLY  
F: 416-438-5513  
E: sales@mollyslip.com

[www.mollyslip.com](http://www.mollyslip.com)

E Oil Supplement

Automatic Transmission Supplement

Manual Transmission Supplement

Copaslip Anti-Seize Compound

Multi-Purpose Grease

Liquid Grease

Combat Penetrating Oil

Tuneslip

Chain Lube

HTBG High Temperature Bearing Grease

Open Gear Spray

Open Gear Lube

Air Drying Film (ADF)

Metal Working Spray

AS/40 Assembly Compound

AS/65 Assembly Compound

Break-In

Moly Powder



# Product Data Sheet

## Open Gear Lube

### Heavy Duty Lubricating Grease with Molybdenum Disulfide

#### Performance

Mollyslip Open Gear Lube is a heavy-duty grease designed to combine heavy duty lubrication under extreme conditions with almost adhesive tenacity to working surfaces. It contains oxidation and rust inhibitors as well as adhesion and EP additives. The result is a lubricant with:

- Resistance to water, acids and alkalis
- High load capacity with mechanical stability
- Low starting torque at low temperatures
- Ability to combat lubricant starvation
- Protection from corrosion
- Ability to cling to surfaces without dripping, draining off or scraping off

#### Features

Mollyslip Open Gear Lube is ideal for use on slow-moving, heavily loaded working surfaces where durability is essential. It is resistant to most acids and alkalis and is completely water resistant, making it effective in adverse weather conditions or contaminated environments.

#### Applications

All open or exposed gears working at a wide range of speeds and any heavily loaded surface.

Industrial: cement works, quarries, mines, paper mills, chemical plants, oil rigs, at sea (including drilling platforms, on docks and on ships).

Automotive: all grease points, particularly fifth wheel plates

Construction and Logging: cranes, excavation equipment, winches, jacks, etc.

#### Specifications

|                                  |                       |
|----------------------------------|-----------------------|
| Consistency N.G.L.I. ....        | No. 2                 |
| Base: .....                      | Bentone               |
| Drop point .....                 | None                  |
| Working penetration @ 77°C ..... | 265/295 @ 25°C (77°F) |
| Closed flashpoint .....          | > 200°C (392° F)      |

#### Packaging

Mollyslip Open Gear Lube is available in:

| Product No. | Packaging                      | Case Size  |
|-------------|--------------------------------|------------|
| 5710 .....  | 400 g (14 oz.) cartridge ..... | Case of 10 |
| 5711 .....  | 454 g (1 lb) plastic jar ..... | Case of 12 |
| 5712 .....  | 2 kg (4.4 lb) metal tin .....  | Case of 6  |
| 5714 .....  | 11.3 kg (25 lb) plastic pail   |            |