

Lubricant Fix

Description

Lubricant Fix is a strongly adherent, high-performance grease for lubricating bearings, hinges and slide guides. Special additives allow high surface loading on slow-running transmissions.

Properties

- outstanding corrosion protection
- does not attack common sealing materials
- stable to oxidation
- good water resistance
- excellent adhesion
- can be delivered by centralized lubrication systems



Available pack sizes

50 g Tube plastic	1080
	D

Technical data

Brief description	K1G-30 DIN 51502
NLGI number	1
Base oil viscosity 40°C	100 mm ² /s
Thickener	Metall / metal
Color / appearance	braun / brown
Operating temperature range	-30 bis +100 °C
Water resistance at 90 °C	0
Worked penetration	310-340
Dropping point	+150 °C

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

For reliable lubrication of bearings, hinges and slide guides. Ideal areas of use: house, yard, garden, hobbies, garage and workshop. Lubricant Fix is also suitable for use as a special grease for lubricating ball bearings operating at high speeds, high temperatures and in corrosive atmospheres.

Application

Thoroughly clean surfaces removing dirt and old grease residues before application. Apply thinly to sliding surfaces and follow the instructions of the bearing and machine manufacturer.