

Product information

Grinding Paste

PI 10/01/06/2016



Description

For effortlessly removing weathered and tarnished paint layers, course dirt, paint-spray mist, scratches and surface cracks. The areas treated with grinding paste can be painted without any additional treatment. Silicon-free. Suitable for polishing machines.

Properties

- suitable for polishing machines
- easy removal of weathered paint layers
- simple to use
- prepares surfaces for painting
- very high standard of quality



Available pack sizes

300 g Tube plastic 1556
D-GB-I-E-P

Technical data

Solubility	teilweise löslich in H ₂ O / partially soluble in water
Form	pastös / pastelike
Density	~1 g/cm ³ DIN 51757
Base	Schleifmittel, Lösungsmittel / grinding agent, solvents
pH value	n.a.
Color / appearance	weiß / white
Flash point	>65 °C DIN ISO 2592
Odor	charakteristisch / characteristic
Viscosity at 20 °C	10000 - 15000 cP
Density at 20 °C	~1 g/cm ³ ISO 787-10

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

Especially for pretreating before paint jobs and to remove paint damage such as scratches and paint spray mist. Suitable for non-ferrous and metallic paint.

Application

Clean surfaces to be treated. Rub Grinding and Polishing Paste into small areas using a cloth or sponge and exerting pressure until the oxidised layers, dirt or scratches have been removed. Carry out subsequent paint care by polishing and preserving.

Comment

Attention when working with polishing machines, as the grinding paste has a very abrasive effect.