

Chain Spray

Description

High-quality thermostable, extremely adherent, throw-proof lubricant compound. After the solvent has evaporated, the product leaves an extremely adherent, soft film of grease. Also suitable for O-ring chains.

Properties

- especially cold, hot and splash-water resistant
- reduces chain elongation
- excellent adhesion
- outstanding corrosion protection
- friction and wear reducing
- excellent penetration action
- highest load-carrying capacity
- resistant to acceleration forces

Technical data

Color / appearance	farblos, klar / colourless, clear
Base	Syntheseöl mit Haftverbesserer / oil with adhesion improver
Density	0,715 g/cm ³
Operating temperature range	-30 bis + 180°C, kurzzeitig bis 200°C / -30 °C to +180 °C, short periods up to 200 °C
Water resistance at 90 °C	0 DIN 51 807
Form	aerosol, flüssig / aerosol, liquid
Odor	charakteristisch / characteristic

Areas of application

Initial and maintenance lubrication of power-transmission chains. Especially suitable for dusty, dirty and corrosive environments. Due to extremely good adherence, especially suitable for high-load, fast-running chains.

Application

Carefully clean chain with solvent such as Rapid Cleaner. Apply by spraying. The lubricant attains its final consistency and adherence once the solvent has rapidly evaporated.



Available pack sizes

200 ml Can aerosol	3581 D-GB-I-E-P
200 ml Can aerosol	2804 D-DK-FIN-N-S
400 ml Can aerosol	3579 D-GB-I-E-P
400 ml Can aerosol	1813 D-NL-F-GR-ARAB

Our information is based on thorough research and may be considered reliable, although not legally binding.