

# Product information

## Hydraulic Lifter Additive

PI 13/03/08/2016



### Description

High performance additive that damps down noise generation of contaminated and sticky hydraulic tappets. Cleans valve bores and thus ensures optimal functioning again.

### Properties

- damps hydraulic tappet noise
- cleans valve bores
- improves the lubrication properties of the oil
- tested for turbochargers and catalytic converters

### Technical data

Color / appearance	hellbraun / light brown
Appearance / properties	viskose Flüssigkeit / viscous liquid
Density at 20 °C	0,887 g/cm <sup>3</sup> DIN 51757
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 20 °C	1100 mPas

### Areas of application

For all gasoline and diesel engines. Can be mixed with all commercially available motor oils

### Application

One 300 ml can of Liqui Moly hydraulic tappet additive is sufficient for up to 6 liters motor oil. The product can be added at any time. After adding, run the engine until warm. For a lasting effect, Liqui Moly Hydraulic tappet additive must be added after each oil change.

### Comment

**Not suitable for use on motorbikes with wet clutches.**



### Available pack sizes

300 ml Can sheet metal	1009 D-F-NL
300 ml Can sheet metal	2770 GB-GR-I
300 ml Can sheet metal	8345 D-PL-BG
300 ml Can sheet metal	8354 D-E-P
300 ml Can sheet metal	8367 GB-ARAB-F
300 ml Can sheet metal	8382 D-H-RO
300 ml Can sheet metal	8338 DK/N-S-FIN
300 ml Can sheet metal	2783 GB-AUS
300 ml Can sheet metal	20004 GB-F-E-USA-CAN
300 ml Can sheet metal	3919 D-RUS-UA
205 l Drum sheet metal	2581 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**