Product information

Multipurpose Grease



Description

High-performance multi-purpose grease for lubricating plain and roller bearings under normal and high loads. Suitable as a universal grease for motor vehicles and for general machine lubrication. Multipurpose Grease ensures long-term lubrication, has good sealing properties, is resistant to damp and dusty environments and moves well in central lubrication systems. Cold and hot water resistant, friction and wear reducing, high pressure and oxidation resistant, work stable as well as protecting from corrosion



Technical data

Pour point -24 °C DIN ISO 3016

Properties

- excellent stability to liquefying
- friction and wear reducing
- good corrosion protection
- highest load-carrying capacity
- especially resistant to cold and hot water
- outstanding slip properties
- optimum stability to aging

Technical data

Brief description K2K-30 DIN 51502

NLGI number 2

DIN 51818

Worked penetration 275-290 1/10 mm

DIN ISO 2137

Dropping point 190 °C

DIN ISO 2176

Oil separation after 7 days $\,$ 5,8 $\,$ %

at 40 °C

DIN 51817

Oil separation after 18

2,2 %

hours at 40 °C

DIN 51817

Flow pressure at -30 °C

<1400 mbar

DIN 51805 n/n

Emcor corrosion class

DIN 51802

Copper corosion after 24

1 b

hours at 100 °C

DIN 51811

Behavior in the presence

of water

DIN 51807 Teil 1

Basisoel

Viscosity at 40 °C 100 mm²/s

ASTM D 7042-04

Flash point 240 °C

DIN ISO 2592

Areas of application

Used for motor vehicles, construction, agricultural machinery, and used in industry. The wide operating temperature range and the high resistance to water reduce the diversity of products required.

Application

As usual for grease. The operating instructions of the bearing and machine manufacturers must be followed.

Available pack sizes

400 g Cartridge plastic 3552

D-GB-I-E-P

400 g Cartridge plastic 1833

D-NL-F-GR-ARAB

400 g Cartridge plastic 7562

D-RUS-UA

1 kg Can sheet metal 1834

D-NL-F-GR-ARAB

1 kg Can sheet metal 3553

D-GB-I-E-P

5 kg Bucket plastic 3554

D-GB

25 kg Bucket plastic

3555 D-GB

50 kg Bucket sheet metal

3556

D-GB

180 kg Drum sheet metal 3557 D-GB

Our information is based on thorough research and may be considered reliable, although not

legally binding.