

Product information

Maintenance Spray, White

PI 6/09/03/2016



Description

Maintenance Spray White is an adherent, waterproof, white, high-performance lubricant. After the solvent has evaporated, the product leaves a soft film of grease.

Properties

- outstanding lubricating action
- good water resistance
- lasting corrosion protection
- excellent high and low temperature behavior
- reduces fretting corrosion
- high bond strength
- clean application
- prevents friction corrosion

Technical data

Color / appearance	weiß / white
Base	Mineralöl, Festschmierstoffe
Thickener	Bentonit
Density	ca. 1,0 g/cm ³
ISO 2176	NLGI 2
Consistency modifiers	ohne / without
Operating temperature range	- 30 bis + 250 / - 30 to + 250 °C
Propellant	Propan, Butan / propane, butane
Odor	charakteristisch / characteristic
Form	flüssig, aerosol / liquid, aerosol
Flash point	-97 °C
Density at 20 °C	0,64 g/ml

Areas of application

Used for lubricating moving parts such as shafts, hinges, joints, pins, Bowden cables, slip rails, chains, springs and lock strikers etc.

Application

Shake can before use. Spray large areas without the capillary tube from about 20-25 cm. The capillary tube eases use in places which are not very accessible.

After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.



Available pack sizes

250 ml Can aerosol	3075 D-GB-I-E-P
50 ml Can aerosol	7556 D-RUS-UA
250 ml Can aerosol	1839 D-NL-F-GR-ARAB
250 ml Can aerosol	2872 D-DK-FIN-N-S
250 ml Can aerosol	3953 D-RUS-UA
250 ml Can aerosol	2712 D-PL-H-RO-TR

Our information is based on thorough research and may be considered reliable, although not legally binding.