

# FLOORING ADHESIVE

## READY-TO-USE ADHESIVE FOR FLOOR COVERINGS, LINOLEUM AND WALL CORK.



### PRODUCT DESCRIPTION

Ready-to-use adhesive for floor coverings, linoleum and wall cork. Waterbased adhesive.

### FIELD OF APPLICATION

Suitable for bonding floor coverings and carpet tiles with jute, felt or textile backing, linoleum and wall cork on porous surfaces such as cement, concrete and wood.

### PROPERTIES

- Easy to apply
- Solvent-free
- Not moisture resistant

### PREPARATION

**Working conditions:** Do not apply at temperatures below +15°C and/or relative humidity higher than 65%.

**Surface requirements:** The surface must be clean, dry, free of dust and grease.

**Preliminary surface treatment:** First level damaged or uneven floors.

**Tools:** Bison Glue spreader No. 2.

### APPLICATION

**Dilute:** If thickened, adhesive may be diluted with water.

**Coverage:** 2-3 m<sup>2</sup>/kg.

#### Directions for use:

Smear the substrate (clean, dry and free of grease) evenly using a Bison glue spreader No.2. Place floor covering, linoleum or wall cork within about 15 minutes into the still wet adhesive and firmly press or roll. During these 15 minutes adjustments can still be made. After 24-48 hours the adhesive bond

can be loaded.

**Open time:** approx. 15 minutes

**Stains/residue:** Remove adhesive residues immediately with water. Dry adhesive residue can only be removed mechanically.

**Points of attention:** When bonding to wooden surfaces endorsement of the seams can occur. The adhesive bond can only be loaded after curing. The smell of the glue disappears after curing as long as the surface is thoroughly dry. We recommend to always observe the instructions of the manufacturer.

### CURE TIMES

**Dry/Cure time:** approx. 24-48 hours

\* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

### TECHNICAL PROPERTIES

**Moisture resistance:** Nil

**Temperature resistance:** -20°C to 50°C

**Chemicals resistance:** Good

### TECHNICAL SPECIFICATIONS

**Chemical base:** Sulfite lye

**Viscosity:** approx. 0 mPa.s., Pasty

**Solid contents:** approx. 79 %

**Density:** approx. 1.61 g/cm<sup>3</sup>

### STORAGE CONDITIONS

At least 24 months after date of manufacture. Store in tightly closed container in a dry, cool and frost-free place.