#### 6300577 -

# **BISON KIT®** super strong, universal, liquid contact adhesive.





and free of grease and dust. Parts should fit together well. For optimal result, degrease first.

TECHNICAL PROPERTIES Moisture resistance: Good Water resistance: Limited UV resistance: Very good

## **TECHNICAL SPECIFICATIONS**

Viscosity: Liquid Solid contents: approx. 24 % Flash point: K1 (<21°C)

**STORAGE CONDITIONS** Store in a dry, cool and frost free place.

### **PRODUCT DESCRIPTION**

Super strong, universal, liquid contact adhesive based on neoprene rubber.

### **FIELD OF APPLICATION**

Bonds plastic panel boards (such as Formica<sup>®</sup>), veneer, hardboard, plastic edges, rubber, leather, linoleum, cork, textiles or polyether foam to itself as well as to wood, chipboard, concrete and metal. Excellent for bonding stair edgings, floor covering or stair carpets, furniture tips or felts, among other things. Also for repairing shoes, bags, toys and carpets, or doing (hobby) handicraft work, for example. Not suitable for polystyrene foam (polystyrene foam - tempex), polyethylene (PE) and polypropylene (PP).

#### PROPERTIES

- · Bonds immediately
- · Super strong
- · Suitable for materials under strain
- · Very universal
- $\cdot$  Liquid
- $\cdot$  Moisture and frost proof
- · Easy to apply
- $\cdot$  Resistant to temperatures between -40°C and +70°C

#### PREPARATION

**Working conditions:** Apply only at temperatures between 15°C and 25°C and a maximum air humidity of 65%. In order to prevent the formation of bubbles due to condensation, the temperature of the adhesive and materials to be bonded should be the same as the ambient temperature and preferably between 18°C and 20°C. Do not place surfaces with an adhesive application in a draught.

Preliminary surface treatment: The materials to be bonded should be dry

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.

6300577.